

Inspection Report

Report No.: XYBA-141128
Supplier : XY-GLOBAL

Inspection Date: 26th Dec-, 2014
Inspector:LEO

Inspection only for: PO : XYBA-141128 Item No. XY21ZC045	Inspection Result: PASS
--	----------------------------

Description	Finished Q'ty	Sample Size	Defect Found	Defects Description	Acceptable Q'ty
XY21ZC045	3000Pcs	7% inspection	0pcs	No failure	3000Pcs

Appearance Inspection :

No failure,

Dimension Inspection:

No failure , below measurement report for reference.

Assembly Test:

No failure

Inspection Summary

The inspection sample plan is 100% inspection.

Digital photo records :



1. Packing



2. Product:



3. Product:

4. Product:



XY21ZC045									
Item	Symbol	Value	Unit	Min	Max	Min	Max	Min	Max
1	Overall Length	40.00	mm	39.95	40.05	39.95	40.05	39.95	40.05
2	Overall Width	20.00	mm	19.95	20.05	19.95	20.05	19.95	20.05
3	Overall Height	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
4	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
5	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
6	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
7	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
8	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
9	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
10	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
11	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
12	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
13	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
14	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
15	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
16	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
17	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
18	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
19	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
20	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
21	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
22	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
23	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
24	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
25	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
26	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
27	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
28	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
29	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05
30	Distance between holes	10.00	mm	9.95	10.05	9.95	10.05	9.95	10.05

5. Product :

6. Inspection report:

	CNC
	AL6061 AL6065AL6063AL7075SUS304SUS303SUS316POM
	CNC
	gague
MOQ	
/	+/- 0.01
	T / T 50 50T / T;
	CNC CNC CNC CNC
	CNC
	20-25T / T 50
	CNC
1.Name OEM CNC	
2.Process CNC	
3.MaterialAL6061 AL6065AL6063AL7075 POM	
4.Surface nickle	
5.Tolerance +/- 0.01	
6 100	
7.SpecificationOEMserice	
8. 2530	
9. CNC accessoried	
10. AustrialEU	
11. ISO 9001	
ISO 1. 10	
2.	
3. surefacefinishment kindlsavailable	
4.	
5.	
6.	
7.	
CNC	
CNC	
CNCISO9001	
CNC	
CNCOEM	